



Insert 995-DG Gulchrom

Varenr.	Størrelse dnom x L (mm)	Hul-størrelse Ø dia.(mm)	Øvrige dimensioner i mm					Vejl. tilladelige belastning i kN*
			a:	b:	c:	f:	h:	
003312060	M 12 x 60	10,2	20,0	16,0	2,75	23,0	13,0	10,0
003312085	M 12 x 85	10,2	35,0	16,0	2,75	23,0	13,0	10,0
003316070	M 16 x 75	13,2	22,0	21,5	3,6	30,00	21,0	16,0
003316100	M 16 x 100	13,2	35,0	21,5	3,6	30,00	21,0	16,0
003320100	M 20 x 90	15,2	25,0	27,0	4,7	38,00	24,0	25,0
003320120	M 20 x 120	15,2	45,0	27,0	4,7	38,00	24,0	25,0
003324120	M 24 x 100	17,2	30,0	32,0	5,4	43,00	24,0	35,0
003330150	M 30 x 135	22,0	35,0	40,0	6,50	57,0	36,0	55,0

* Disse værdier er kun gældende med monteret tværpind



Insert 995-DGA Gulchrom, med påsvejst tværpind L=100 mm

Varenr.	Størrelse dnom x L mm:	Øvrige dimensioner i mm					Vejl. tilladelige belastning i kN
		a:	b:	c:	f:	h:	
005312060	M 12 x 60	20,0	16,0	2,75	23,0	13,0	10
005312085	M 12 x 85	35,0	16,0	2,75	23,0	13,0	10
005316075	M 16 x 75	22,0	21,5	3,60	30,0	21,0	16
005316100	M 16 x 100	35,0	21,5	3,60	30,0	21,0	16
005320120	M 20 x 120	45,0	27,0	4,65	38,0	24,0	25



Insert 995-DG i syrefast rustfri A4 (AISI-316)

Varenr.	Størrelse dnom x L mm:	Hul-størrelse Ø dia. (mm)	Udv. Dia.(mm)
009312060	M 12 x 60	10,0	18,0
009312080	M 12 x 80	10,0	18,0
009316080	M 16 x 80	12,0	25,0
009316100	M 16 x 100	12,0	25,0
009316120	M 16 x 120	12,0	25,0
009320100	M 20 x 100	14,0	30,0
009320120	M 20 x 120	14,0	30,0
009324130	M 24 x 130	16,0	35,0
009330135	M 30 x 135	18,0	45,0