



Insert 995-G Gulchrom

Varenr.	Størrelse dnom x L		Øvrige dimensioner i mm					Vejl. tilladelige belastning i kN
	mm:	Hul str. Ø (mm)	a:	b:	c:	f:	h:	
003206040	M 6 x 40	6,0	20,0	8,5	1,0	12,5	7,0	1,5
003208050	M 8 x 50	8,1	25,0	10,5	1,0	16,0	8,0	2,5
003210050	M 10 x 50	6,2	20,0	13,5	1,5	20,0	12,0	3,5
003212060	M 12 x 60	7,2	23,0	17,0	2,0	25,0	15,0	5
003212070	M 12 x 70	9,2	30,0	17,0	2,0	25,0	17,0	6
003216070	M 16 x 70	9,2	25,0	21,3	3,2	30,0	17,0	7
003216080	M 16 x 80	12,2	25,0	21,3	3,2	30,0	22,0	8
003216100	M 16 x 100	9,2	32,0	21,3	3,2	30,0	22,0	10
003216120	M 16 x 120	12,2	45,0	21,3	3,2	30,0	22,0	12
003220100	M 20 x 100	12,2	40,0	26,9	2,6	39,0	22,0	12,5
003220120	M 20 x 120	14,2	40,0	26,9	2,6	39,0	22,0	14
003224120	M 24 x 120	14,2	50,0	33,7	4,0	48,0	25,0	18

Insert 995-G Rustfri A4 (AISI-316TI)

Varenr.	Størrelse dnom x L		Øvrige dimensioner i mm					Vejl. tilladelige belastning i kN
	mm:	Hul str. Ø (mm)	a:	b:	c:	f:	h:	
009208050	M 8 x 50	7,0	20,0	10,5	1,0	16,0	7,0	2,5
009210050	M 10 x 50	6,2	20,0	13,5	1,5	20,0	11,0	3,5
009212060	M 12 x 60	9,2	25,0	16,0	1,5	25,0	13,0	5
009216100	M 16 x 100	12,2	25,0	21,3	2,6	31,0	20,0	8
009220100	M 20 x 100	14,2	40,0	26,9	2,6	39,0	23,0	12,5
009224120	M 24 x 120	14,2	50,0	33,7	3,2	49,0	28,0	18



Insert 995-A Gulchrom, med påsvejst tværpind

Varenr.	Størrelse dnom x L		Øvrige dimensioner i mm					Vejl. tilladelige belastning i kN
	mm:		a:	b:	c:	f:	h:	
0054120700	M 12 x 70		30,0	17,0	2,0	25,0	17,0	6
005416080	M 16 x 80		25,0	21,3	3,2	30,0	22,0	8
005416100	M 16 x 100		32,0	21,3	3,2	30,0	22,0	10
005420100	M 20 x 100		40,0	26,9	2,6	39,0	22,0	12,5
005424120	M 24 x 120		50,0	33,7	4,0	48,0	25,0	18