



Skive DIN-125, Elgalvaniseret

Varenr.	Hul dia. Ø mm	Udv. Ø mm	Tykkelse mm
31004000E	4,3	9,0	0,8
31005000E	5,3	10,0	1,0
31006000E	6,4	12,0	1,6
31008000E	8,4	16,0	1,6
31010000E	10,5	20,0	2,0
31013000E	13,0	24,0	2,5
31017000E	17,0	30,0	3,0
31021000E	21,0	37,0	3,0
31025000E	25,0	44,0	4,0
31031000E	31,0	56,0	4,0

Skive DIN-125, Varmgalvaniseret

Varenr.	Hul dia. Ø mm	Udv. Ø mm	Tykkelse mm
31006000V	6,4	12,0	1,6
31008000V	8,4	16,0	1,6
31010000V	10,5	20,0	2,0
31012000V	13,0	24,0	2,5
31017000V	17,0	30,0	3,0
31021000V	21,0	37,0	3,0
31025000V	25,0	44,0	4,0
31027000V	28,0	50,0	4,0
31031000V	31,0	56,0	4,0
31036000V	37,0	66,0	5,0
31043000V	43,0	78,0	7,0

Skive DIN-125, Rustfri A2

Varenr.	Hul dia. Ø mm	Udv. Ø mm	Tykkelse mm
31004000R	4,3	9,0	0,8
31006000R	6,4	12,0	1,6
31008000R	8,4	16,0	1,6
31010000R	10,5	20,0	2,0
31012000R	13,0	24,0	2,5
31017000R	17,0	30,0	3,0
31021000R	21,0	37,0	3,0
31025000R	25,0	44,0	4,0
31031000R	31,0	56,0	4,0

Skive DIN-125, syrefast rustfri A4

Varenr.	Hul dia. Ø mm	Udv. Ø mm	Tykkelse mm
31004000S	4,3	9,0	0,8
31005000S	5,3	10,0	1,0
31006000S	6,4	12,0	1,6
31008000S	8,4	16,0	1,6
31010000S	10,5	20,0	2,0
31012000S	13,0	24,0	2,5
31017000S	17,0	30,0	3,0
31021000S	21,0	37,0	3,0
31025000S	25,0	44,0	4,0
31031000S	31,0	56,0	4,0