



Gennemstiksanker, elgalvaniseret (Elz.)

| Varenr. | Dimension | Bor Ø (mm) | Borhuls-dybde (mm) | Max. Emne-tykkelse (mm) | Til-spændingsmoment (Nm) | Vejledende tilladelig belastning i kN | |
|-----------|------------|------------|--------------------|-------------------------|--------------------------|---------------------------------------|----------|
| | | | | | | Træk | Tværlast |
| 70806055E | M 6 x 55 | 6 | 50 | 10 | 6 | 3,3 | 4,0 |
| 70806085E | M 6 x 85 | 6 | 55 | 30 | 6 | 3,3 | 4,0 |
| 70806100E | M 6 x 100 | 6 | 55 | 45 | 6 | 3,3 | 4,0 |
| 70808050E | M 8 x 50 | 8 | 40 | 5 | 18 | 2,0 | 1,8 |
| 70808080E | M 8 x 75 | 8 | 55 | 10 | 18 | 3,3 | 3,8 |
| 70808100E | M 8 x 100 | 8 | 65 | 15 | 18 | 4,0 | 4,2 |
| 70808115E | M 8 x 115 | 8 | 65 | 30 | 18 | 4,0 | 4,2 |
| 70808130E | M 8 x 130 | 8 | 65 | 50 | 18 | 4,0 | 4,2 |
| 70810120E | M 10 x 120 | 10 | 70 | 10 | 30 | 5,0 | 6,2 |
| 70810160E | M 10 x 150 | 10 | 70 | 55 | 30 | 5,0 | 6,2 |
| 70812080E | M 12 x 80 | 10 | 70 | 90 | 30 | 5,0 | 6,2 |
| 70812110E | M 12 x 110 | 12 | 70 | 5 | 50 | 4,0 | 4,2 |
| 70812140E | M 12 x 140 | 12 | 80 | 20 | 50 | 8,0 | 9,5 |
| 70812155E | M 12 x 160 | | | | | | |
| 70812180E | M 12 x 180 | 12 | 80 | 50 | 50 | 8,0 | 9,5 |
| 70816090E | M 16 x 90 | 12 | 80 | 85 | 50 | 8,0 | 11,0 |
| 70816110E | M 16 x 110 | 16 | 80 | 10 | 100 | 8,5 | 11,0 |
| 70816125E | M 16 x 125 | 16 | 100 | 15 | 100 | 8,5 | 16,0 |
| 70816145E | M 16 x 145 | 16 | 115 | 25 | 100 | 12,0 | 16,0 |
| 70816175E | M 16 x 170 | 16 | 115 | 70 | 100 | 12,0 | 16,0 |
| 70816220E | M 16 x 220 | 16 | 115 | 110 | 100 | 12,0 | 20,0 |
| 70820120E | M 20 x 120 | 20 | 100 | 10 | 240 | 16,0 | 20,0 |
| 70820180E | M 20 x 170 | 20 | | | | | |

Gennemstiksanker, varmgalvaniseret (Fzv.)

| Varenr. | Dimension | Bor Ø (mm) | Borhuls-dybde (mm) | Max. Emne-tykkelse (mm) | Til-spændingsmoment (Nm) | Vejledende tilladelig belastning i kN | |
|-----------|------------|------------|--------------------|-------------------------|--------------------------|---------------------------------------|----------|
| | | | | | | Træk | Tværlast |
| 70808065V | M 8 x 60 | 8 | 50 | 5 | 20 | 4,6 | 4,6 |
| 70808080V | M 8 x 75 | 8 | 65 | 5 | 20 | 5,8 | 5,4 |
| 70808115V | M 8 x 115 | 8 | 55 | 5 | 30 | 5,0 | 6,2 |
| 70810070V | M 10 x 70 | 10 | 55 | 5 | 35 | 5,1 | 6,1 |
| 70810090V | M 10 x 90 | 10 | 70 | 10 | 35 | 6,4 | 8,5 |
| 70810125V | M 10 x 120 | 10 | 70 | 40 | 35 | 6,4 | 8,5 |
| 70812090V | M 12 x 90 | 12 | 75 | 5 | 60 | 9,0 | 10,8 |
| 70812110V | M 12 x 110 | 12 | 85 | 18 | 60 | 10,0 | 12,0 |
| 70812130V | M 12 x 140 | 12 | 85 | 48 | 60 | 10,0 | 12,0 |
| 70816125V | M 16 x 125 | 16 | 110 | 5 | 120 | 14,0 | 22,0 |
| 70816150V | M 16 x 145 | 16 | 110 | 25 | 120 | 14,0 | 22,0 |



Gennemstiksanker, Rustfri syrefast A4

| Varenr. | Dim. | Bor Ø (mm) | Borhuls-dybde (mm) | Max. Emne-tykkelse (mm) | Til-spændings-moment (Nm) | Vejledende tilladelig belastning i kN | |
|-----------|------------|------------|--------------------|-------------------------|---------------------------|---------------------------------------|----------|
| | | | | | | Træk | Tværlast |
| 70806045S | M 6 x 45 | 6 | 40 | 2 | 7 | 3,0 | 2,9 |
| 70806055S | M 6 x 60 | 6 | 55 | 2 | 7 | 4,3 | 2,9 |
| 70806085S | M 6 x 80 | 6 | 55 | 22 | 7 | 4,3 | 2,9 |
| 70808050S | M 8 x 50 | 8 | 40 | 5 | 20 | 2,7 | 2,7 |
| 70808080S | M 8 x 75 | 8 | 65 | 5 | 20 | 5,8 | 5,3 |
| 70808090S | M 8 x 90 | 8 | 65 | 20 | 20 | 5,8 | 5,3 |
| 70808130S | M 8 x 130 | 8 | 50 | 5 | 20 | 5,0 | 6,2 |
| 70810075S | M 10 x 70 | 10 | 55 | 5 | 35 | 5,1 | 6,2 |
| 70810090S | M 10 x 90 | 10 | 70 | 10 | 35 | 6,4 | 8,4 |
| 70810120S | M 10 x 120 | 10 | 70 | 40 | 35 | 6,4 | 8,4 |
| 70812080S | M 12 x 75 | 12 | 60 | 5 | 60 | 5,7 | 6,9 |
| 70812110S | M 12 x 110 | 12 | 85 | 18 | 60 | 10,0 | 12,2 |
| 70812140S | M 12 x 140 | 12 | 85 | 48 | 60 | 10,0 | 2,2 |
| 70816100S | M 16 x 90 | 16 | 75 | 5 | 120 | 7,0 | 8,3 |
| 70816145S | M 16 x 145 | 16 | 110 | 25 | 120 | 14,0 | 22,8 |
| 70816170S | M 16 x 170 | 16 | 110 | 48 | 120 | 14,0 | 22,8 |
| 70820160S | M 20 x 170 | 20 | 135 | 23 | 240 | 20,0 | 35,6 |