



### Slagankre, elgalvaniseret

Varenr.	Dimension	Bor Ø (mm)	Borhulsdybde (mm)	Max. Emnetykkelse (mm)	Tilspændingsmoment (Nm)	Vejledende tilladelig belastning i kN	
						Træk	Tværlast
70106025E	M 6 x 25	8	30	11	5	2.0	2.0
70108030E	M 8 x 30	10	35	13	10	2.5	2.5
70110040E	M 10 x 40	12	45	15	20	4.0	4.0
70112050E	M 12 x 50	15	55	18	40	6.0	6.0
70116060E	M 16 x 60	20	65	23	80	11.0	11.0
70120080E	M 20 x 80	25	85	34	16	16.0	16.0



### Slagankre med krave, elgalvaniseret

Varenr.	Dimension	Bor Ø (mm)	Borhulsdybde (mm)	Max. Emnetykkelse (mm)	Tilspændingsmoment (Nm)	Vejledende tilladelig belastning i kN	
						Træk	Tværlast
70108030KE	M 8 x 30	10	35	13	10	2.5	2.5
70110040KE	M 10 x 40	12	45	15	20	4.0	4.0
70112050KE	M 12 x 50	15	55	18	40	6.0	6.0
70112050KE-Ø16	M 12 x 50	16	55	18	40	6.0	6.0
70116060KE	M 16 x 60	20	65	23	80	11.0	11.0



### Montagedorn

Varenr.	Dimension
070506000	M 6
070508000	M 8
070510000	M 10
070512000	M 12
070516000	M 16
070520000	M 20